

PALOMAT® 1/2 Pallets

Efficient pallet flow - no manual lifting of pallets

Fully automatic stacking and destacking

You insert or remove the pallets using a hand pallet truck, electric stacker or a full-size forklift truck. All handling is carried out at floor level. The PALOMAT 1/2 Pallets detects the 1/2-pallets via photo sensors after which they are fully automatic stacked or destacked one by one.

When selecting destacking, a stack of no more than 15 1/2-pallets will be inserted in the PALOMAT®, after which the pallets are fully automatic destacked one by one. When selecting stacking, the 1/2-pallets are inserted one by one, after which the pallets are fully automatic stacked to no more than 15 pallets. The entire stack can subsequently be removed.

PALOMAT® 1/2 Pallets is only operated manually using the touch panel when there is to be a change between stacking and destacking or vice versa. In addition to this, the PALOMAT 1/2 Pallets operates fully automatic.

The PALOMAT can handle all 4-way pallets in wood, plastic and metal no matter what the length, width or height.

We can customise the PALOMAT to exactly match the pallet size you use.



Your benefits with PALOMAT®

- Space saving and a tidy workplace
- · Optimised pallet flow
- · Improved work environment
- Reduced pallet costs
- · Increased efficiency
- · No manual pallet handling
- · Less absence due to illness
- · Reduced time spent per pallet
- Fewer back injuries, jammed fingers and feet
- · Less truck driving
- · Leaner increased efficiency with less resources
- "Plug and Play" solution









Models				
Article no.	Machine dimensions L x W x H (mm)	Pallet size L x W x H (mm)	Lifting capacity	No. of pallets
152050	935x1450x2350*	600x800x150	500 kg	15 pallets
150050	935x1450x2350*	600x800x150	500 kg	15 pallets

* Incl. safety frame for 15 pallets with gate which is required
, , , , , , , , , , , , , , , , , , , ,

Technic	Option		
Power source	Pallet handling in cold environments		
220-240V AC, 50 Hz	Down to - 25 C°/ - 13 F°		
6-7 bar + 100-240V AC, 50 - 60Hz			

Control: Siemens S7-1200 Actuator: Linak Pneumatics: SMC

Standard colours: RAL 3002 red, RAL 5002 blue, RAL 7032 grey and RAL 7035 grey



